

Issuing Date 16-May-2014

Revision Date 16-May-2014

Revision Number 0

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

Product Name Dykem Remover and Prep Bulk

Other means of identification

Part Number 82638, 82738, 82838, 82938

Formula Code 8947

UN-Number UN1263

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Remover & Cleaner

Uses advised against No information available

Supplier's details

Supplier Address

ITW Professional Brands
805 E. Old 56 Highway
Olathe, KS 66061
TEL: 1-800-443-9536

Emergency telephone number

Emergency Telephone Number 800-535-5053 Infotrac

2. HAZARDS IDENTIFICATION

Classification

This chemical is considered hazardous according to the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200)

Serious Eye Damage/Eye Irritation	Category 2
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Flammable liquids	Category 2

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word Danger

Hazard Statements

- Causes serious eye irritation
- May cause drowsiness or dizziness
-
- Highly flammable liquid and vapor.

**Appearance** Clear**Physical State** Liquid.**Odor** Solvent**Precautionary Statements****Prevention**

- Keep away from heat/sparks/open flames/hot surfaces - No smoking
- Keep container tightly closed
- Keep cool
- Ground/bond container and receiving equipment
- Use explosion-proof electrical/ventilating/lighting/equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Wash face, hands and any exposed skin thoroughly after handling
- Use only outdoors or in a well-ventilated area
- Wear protective gloves/protective clothing/eye protection/face protection.

General Advice

- None

Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention.

Skin

- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Inhalation

- Call a POISON CENTER or doctor/physician if you feel unwell
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Fire

- In case of fire: Use CO2, dry chemical, or foam for extinction.

Storage

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Hazard Not Otherwise Classified (HNOC)

Not applicable

Other information

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Trade secret
Acetone	67-64-1	40-70	*
Ethanol	64-17-5	15-40	*
n-Propyl acetate	109-60-4	1-5	*
Isopropyl alcohol	67-63-0	1-5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of necessary first-aid measures

General Advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Seek immediate medical attention/advice.
Skin Contact	Wash off immediately with plenty of water. If skin irritation persists, call a physician.
Inhalation	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms persist, call a physician.
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Consult a physician if necessary
Protection of First-aiders	Use personal protective equipment. Remove all sources of ignition.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects No information available.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray. Carbon dioxide (CO₂). Dry chemical. Alcohol-resistant foam.

Unsuitable Extinguishing Media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Extremely flammable. Keep product and empty container away from heat and sources of ignition. Risk of ignition Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks).

Explosion Data

Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	Yes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Keep people away from and upwind of spill/leak. Take precautionary measures against static discharges. Pay attention to flashback.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Small spillage: Take up with sand or other noncombustible absorbent material and place into containers for later disposal. Large spillage: Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Pick up and transfer to properly labeled containers. Dispose of promptly.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Do not breathe vapors or spray mist. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Use only in area provided with appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat and sources of ignition. Keep out of the reach of children. Keep container closed when not in use.

Incompatible Products Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m ³
Ethanol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm 10% LEL TWA: 1000 ppm TWA: 1900 mg/m ³

Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm 10% LEL TWA: 980 mg/m ³ TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m ³
n-Propyl acetate 109-60-4	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 840 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 840 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 1050 mg/m ³	IDLH: 1700 ppm TWA: 200 ppm TWA: 840 mg/m ³ STEL: 250 ppm STEL: 1050 mg/m ³

Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Safety glasses with side-shields. If splashes are likely to occur, wear: Chemical splash goggles.

Skin and Body Protection Chemical resistant gloves Apron. Boots.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Hygiene Measures When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Appearance	Clear
Odor	Solvent	Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	No data available	None known
Melting Point/Range	No data available	None known
Boiling Point/Boiling Range	56.1 °C / 132.98 °F	None known
Flash Point	-20 °C / -4 °F	Tag closed cup For acetone.
Evaporation rate	> 1 (BuAc=1)	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available 21.2	
lower flammability limit	No data available 1.7	
Vapor Pressure	No data available	None known
Vapor Density	> 1 (air = 1)	None known
Specific Gravity	No data available.	None known
Water Solubility	Completely soluble	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	Water thin	None known

Flammable Properties Flammable liquid. HIGHLY FLAMMABLE: Will be easily ignited by heat, sparks or flames.

Explosive Properties No data available
Oxidizing Properties No data available

Other information

VOC Content (%) 36.23%
VOC (g/l) 287 g/l

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Heat, flames and sparks. Incompatible products.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong reducing agents. Strong alkalis.

Hazardous decomposition products

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke) Soot.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	May cause irritation of respiratory tract. May cause drowsiness and dizziness.
Eye Contact	Causes serious eye irritation.
Skin Contact	May cause irritation.
Ingestion	Ingestion of liquid may cause vomiting.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetone	= 5800 mg/kg (Rat)	1700mg/kg (rabbit)	18892 mg/m ³
Ethanol	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
Isopropyl alcohol	= 4396 mg/kg (Rat)	12800 mg/kg (Rat) 12870 mg/kg (Rabbit)	72.6 mg/L (Rat) 4 h
n-Propyl acetate	= 9370 mg/kg (Rat)	> 17760 mg/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects and also chronic effects from short and long term exposure

Sensitization	No information available.
Mutagenic Effects	No information available.
Carcinogenicity	Ethanol has been shown to be carcinogenic in long-term studies only when consumed and abused as an alcoholic beverage.

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethanol	A3	Group 1	Known	X
Isopropyl alcohol				X

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Chronic Toxicity	Avoid repeated exposure. Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage.
Target Organ Effects	Respiratory system. Eyes. Skin. Central nervous system (CNS).
Aspiration Hazard	No information available.

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document:

LD50 Oral	6163 mg/kg
LD50 Dermal	711111 mg/kg mg/L
dust/mist	384.9 mg/L
Vapor	3089.5 mg/L

12. ECOLOGICAL INFORMATION**Ecotoxicity**

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Acetone 67-64-1		LC50 96 h: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) LC50 96 h: 6210 - 8120 mg/L static (Pimephales promelas) LC50 96 h: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	EC50 48 h: 10294 - 17704 mg/L Static (Daphnia magna) EC50 48 h: 12600 - 12700 mg/L (Daphnia magna)
Ethanol 64-17-5		LC50 96 h: 12.0 - 16.0 mL/L static (Oncorhynchus mykiss) LC50 96 h: > 100 mg/L static (Pimephales promelas) LC50 96 h: 13400 - 15100 mg/L flow-through (Pimephales promelas)	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	LC50 48 h: 9268 - 14221 mg/L (Daphnia magna) EC50 24 h: = 10800 mg/L (Daphnia magna) EC50 48 h: = 2 mg/L Static (Daphnia magna)

Isopropyl alcohol 67-63-0	EC50 96 h: > 1000 mg/L (Desmodesmus subspicatus) EC50 72 h: > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h: = 11130 mg/L static (Pimephales promelas) LC50 96 h: = 9640 mg/L flow-through (Pimephales promelas) LC50 96 h: > 1400000 µg/L (Lepomis macrochirus)		EC50 48 h: = 13299 mg/L (Daphnia magna)
n-Propyl acetate 109-60-4		LC50 96 h: 56-64 mg/L flow-through (Pimephales promelas) LC50 96 h: 56-64 mg/L static (Pimephales promelas)		EC50 24 h: = 318 mg/L (Daphnia magna)

Persistence and Degradability No information available.

Bioaccumulation

Chemical Name	Log Pow
Acetone	-0.24
Ethanol	-0.32
Isopropyl alcohol	0.05

Other Adverse Effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with federal, state, and local regulations

Contaminated Packaging Do not re-use empty containers.

US EPA Waste Number D001
U002

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone - 67-64-1		Included in waste stream: F039		U002

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Acetone	Ignitable
Ethanol	Toxic Ignitable
Isopropyl alcohol	Toxic Ignitable
n-Propyl acetate	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN-Number UN1263
Proper shipping name Paint related material
Hazard Class 3
Packing Group II
Reportable Quantity (RQ) Acetone: RQ kg= 3546.88
Description UN1263, Paint related material, 3, II, RQ
Emergency Response Guide Number 128

TDG

UN-Number UN1263

Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	II
Description	UN1263, Paint related material, 3, II

<u>MEX</u>	
UN-Number	UN1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	II
Description	UN1263, Paint related material, 3, II

<u>ICAO</u>	
UN-Number	UN1263
Proper shipping name	Paint related material
Hazard Class	3
Packing Group	II
Description	UN1263, Paint related material, 3, II

<u>IATA</u>	
UN-Number	UN1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	II
ERG Code	3L
Description	UN1263, Paint related material, 3, II

<u>IMDG/IMO</u>	
UN-Number	UN1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	II
EmS No.	F-E, S-E
Description	UN1263, Paint related material, 3, II, (-20°C c.c.)

<u>RID</u>	
UN-Number	UN1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	II
Classification Code	F1
Description	UN1263, Paint related material, 3, II

<u>ADR</u>	
UN-Number	UN1263
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	II
Classification Code	F1
Tunnel Restriction Code	(D/E)
Description	UN1263, Paint related material, 3, II, (D/E)
ADR/RID-Labels	3

<u>ADN</u>	
Proper Shipping Name	Paint related material
Hazard Class	3
Packing Group	II
Classification Code	F1
Special Provisions	163, 640C, 650

Description	UN1263, Paint related material , 3, II
Limited Quantity	5 L
Ventilation	VE01

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	Complies
EINECS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Isopropyl alcohol	67-63-0	1.8	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Acetone	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals: Ethyl alcohol is only considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage.

Chemical Name	CAS-No	California Prop. 65
Ethanol	64-17-5	Developmental

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Acetone	X	X	X		X
Ethanol	X	X	X		
Isopropyl alcohol	X	X	X		X
n-Propyl acetate	X	X	X		X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

<u>NFPA</u>	Health Hazard 2	Flammability 3	Instability 0	Physical and Chemical Hazards -
<u>HMIS</u>	Health Hazard 2	Flammability 3	Physical Hazard 0	Personal Protection X

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 16-May-2014
Revision Date 16-May-2014
Revision Note Initial Release.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet