



LT Threading – Toolholder Identification System

METRIC

INCH

S = insert screw or clamp only

straight shank

AS

offset shank

S

DH

C – qualified back and end, 5" long
D – qualified back and end, 6" long
E – qualified back and end, 7" long
T – qualified back and end, 3.250" long
Q – qualified metric holder

2. Insert Holding Method

L S

3. Tool Style

AS R

5. Drop Head

2525K 16

8. Qualified Surface and Length

16 3 D

1. Insert Style

L = laydown triangle

4. Hand of Tool

left hand

L

right hand

R

6. Shank Size

metric:
Shank height and width in mm and holder length according to ISO standard
inch:
This position will show a significant two-digit number that indicates the holder cross section. For shanks 5/8" square and over, the number will represent the number of sixteenths of width and height. For shanks under 5/8" square, the number of sixteenths of cross section will be preceded by a zero. For rectangular holders, the first digit represents the number of eighths of width, and the second digit the number of quarters of height, except for a toolholder 1 1/4" x 1 1/2", which is given the number 91.

7. Insert Size

Size equals number of 1/8-inch increments of IC.

inch insert size	metric insert size	D (inch)	LI (mm)
2	11	1/4	11,0
3	16	3/8	16,5
4	22	1/2	22,0

*NOTE: Toolholders with primary shank sizes larger than 1/2-inch or 12 mm are supplied with clamp and insert screw. Secure the insert with either the clamp or insert screw. Do not use both.

LT Threading – Shim Identification System

1. Shim

SM

2. Y – Shim for LT Standard Inserts

Y

3. E – External I – Internal

E

4. Insert Size

3

D value in 1/8ths inch

5. Shim Angle

2P

2P– 2° positive
1P– 1° positive
— 0° neutral
1N– 1° negative
2N– 2° negative
3N– 3° negative

NOTE: For shims and shim kits, see page C61 - C63